



File Name: bose sa3 amp manual.pdf

Size: 3011 KB

Type: PDF, ePub, eBook

Category: Book

Uploaded: 1 May 2019, 22:31 PM

Rating: 4.6/5 from 648 votes.

Status: AVAILABLE

Last checked: 11 Minutes ago!

In order to read or download bose sa3 amp manual ebook, you need to create a FREE account.

[Download Now!](#)

eBook includes PDF, ePub and Kindle version

[Register a free 1 month Trial Account.](#)

[Download as many books as you like \(Personal use\)](#)

[Cancel the membership at any time if not satisfied.](#)

[Join Over 80000 Happy Readers](#)

Book Descriptions:

We have made it easy for you to find a PDF Ebooks without any digging. And by having access to our ebooks online or by storing it on your computer, you have convenient answers with bose sa3 amp manual . To get started finding bose sa3 amp manual , you are right to find our website which has a comprehensive collection of manuals listed.

Our library is the biggest of these that have literally hundreds of thousands of different products represented.



Book Descriptions:

bose sa3 amp manual

WA R N I N G The apparatus shall not be exposed to dripping or splashing, and objects filled with liquids, such as vases, shall not be placed on the apparatus. As with any electronic products, use care not to spill liquids into any part of the system. These CAUTION marks are located on the enclosure of your product. The exclamation point within an equilateral triangle, as marked on the system, is intended to alert the user to the presence of important operating and maintenance instructions in this owner's guide. The lightning flash with arrowhead symbol within an equilateral triangle alerts the user to the presence of uninsulated dangerous voltage within the system enclosure that may be of sufficient magnitude to constitute a risk of electrical shock. Class B emissions This Class B digital apparatus meets all requirements of the Canadian Interference Causing Equipment Regulations. CAUTION To prevent electrical shock, match the wide blade of the line cord plug to the wide slot of the AC main receptacle. Insert fully. CAUTION This product is not designed for use in recreational vehicle or marine applications. **WA R N I N G** No naked flame sources, such as lighted candles, should be placed on the apparatus. Note The product label is located on the bottom of the product. Please read this owner's guide. Please take the time to follow the instructions in this owner's guide carefully. It will help you set up and operate your system properly and enjoy all of its advanced features. Please save this owner's guide for future reference. All trademarks referenced herein are property of Bose Corporation. All rights reserved. Bose, Acoustimass, Lifestyle, Personal and Wave are registered trademarks of Bose Corporation. For example, do not place the product on a bed, sofa, or similar surface that may block the ventilation openings. <http://www.rbconnections.co.uk/uploads/conflo-iv-manual.xml>

- **bose sa3 amp manual, bose lifestyle sa-3 amplifier manual, bose sa 3 amplifier manual, bose sa3 user manual, bose sa3 amplifier service manual, bose sa 3 amp service manual, bose sa3 amp manual, bose lifestyle sa3 amp manual.**

Do not put it in a built-in system, such as a bookcase or a cabinet that may keep air from flowing through its ventilation openings. 8. Do not install near any heat sources, such as radiators, heat registers, stoves or other apparatus including amplifiers that produce heat. 9. Do not defeat the safety purpose of the polarized or grounding-type plug. A polarized plug has two blades with one wider than the other. A grounding-type plug has two blades and a third grounding prong. The wider blade or third prong are provided for your safety. Opening or removing covers may expose you to dangerous voltages or other hazards. This will provide some protection against voltage surges and built-up static charges. Refer to the antenna grounding illustration on this page. Note to CATV system installer This reminder is provided to call the CATV system installer's attention to Article 820.40 of the NEC of USA that provides guidelines for proper grounding. In particular, it specifies that the cable ground shall be connected to the grounding system of the building, as close to the point of cable entry as is practical. Information about products that generate electrical noise If applicable, this equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, this is no guarantee that interference will not occur in a particular installation. Note Unauthorized modification of the receiver or radio remote control could void the user's authority to operate this equipment. <http://www.lospinello.it/public/news/conflict-transformation-and-restorative-justice-manu>

This product complies with the Canadian ICES003 Class B specifications. Antenna lead-in wire
Antenna discharge unit NEC Section 81.020 Grounding conductor NEC Section 810.21 Ground
clamps Power service grounding electrode system NEC Article 250, Part H Electric service equipment
Ground clamp Unpacking the carton WARNING To avoid danger of suffocation, keep the
plastic bags out of the reach of children. Carefully unpack the shipping carton. You may need
them later. The original packing materials provide the safest way to transport this product.
Note Locate the serial number on the bottom panel of the amplifier, and write it in the appropriate
blank on page 3. If any part of the product appears to be damaged, do not attempt to use it.
Contact your authorized Bose dealer immediately, or call Bose Customer Service. Refer to the address
list enclosed in the product packaging for correct phone numbers. If the power cord
does not fit your power main outlet, DO NOT alter the plug in any way. Contact Bose Customer
Service for assistance. Allow you to control the volume in a room using a wall-mounted control.
See the contact list inside the back cover of this guide. **SPEAKER OUTPUTS** Left and right amplifier
speaker outputs. A 60 ohm minimum load is required. To determine the correct speaker wire
size, see "Wire recommendation" on page 29. 1 2 3 4 5 6 7 1 2 3 See "Powering up your system"
on page 22. **AUX INPUT SA3** only Left and right channel line inputs for a local audio device. Input
signals are passed through to the output jack to allow daisy chaining. 4 C 6 7 8 9 A B C 6 7 8 9
SA2 SA3 For switches 6 through 9, see "Setting up the amplifier room code" on page 25. For
switches A, B, and C, see "Setting Up Advanced Features" on page 26. 5 6 7 The set of instructions
you need depends on whether you have a media center, music center, or multi-room interface.

The product label on the bottom panel identifies the model you have. For the AV28 media center,
see "Model AV28 media center setup" on page 13. For the multi-room interface, see "Multi-room
interface setup" on page 15. For the Model 20 music center, see "Model 20 music center setup"
on page 17. For the Model 5 music center, see, "Model 5 music center setup" on page 19. Note If you
are planning to use this amplifier beyond a second room, you will need to change some switch
settings in the amplifier and remote. **CAUTION** DO NOT mount the amplifier on surfaces that are
not sturdy enough, or that have hazards concealed behind them, such as electrical wiring or
plumbing. **CAUTION** The amplifier must be used indoors. It is important to prevent moisture
from getting into the unit. Note If this remote is to be used beyond a second room, other
switch settings will need to be changed. See "Setting Up Additional Rooms For Sound" on page
23. **ON** House code switches must match main room remote Figure 11 Sample display for a two
room system Press the ROOM button to control a single room or two or more rooms that share
a source. Press the HOUSE button to control all connected rooms as one. The room indicators
tell you what was selected by the ROOM or HOUSE button. **DO NOT** plug the amplifier into an
outlet until you have completed all other connections. Insert the white RCA piggyback
connector into the L left FIXED OUTPUT jack. Insert the 3.5 mm miniplug into the SYSTEM
CONTROL 2 jack on the rear panel of the music center. 3. Insert the red RCA connector of the
Acoustimass module cable into the red piggyback jack and the white RCA connector into the
white piggyback jack. 4. Plug one end of the 20-foot audio cable supplied in to the free end of
the three-foot audio input adapter cable.

<http://www.bosport.be/newsletter/3l-manual>

CAUTION Make sure that the amplifier is disconnected from AC power before making speaker
connections. Speaker cord consists of two insulated wires. Continuously lit Amplifier is on and
ready to produce sound. Lit but rapidly flickering Amplifier is configured as a supplemental
amplifier. Status LED See "Single and supplemental amplifiers" on page 26. Figure 20 Amplifier
room code settings C 6 7 8 9 A B C 6 7 8 9 SA2 SA3 Room code switches Room 6789 B Down Down
Down Up C Down Down Up Down D Down Down Up Up E Down Up Down Down F Down Up Down

Up G Down Up Up Down H Down Up Up Up I Up Down Down Down J Up Down Down Up K Up Down Up Down L Up Down Up Up M Up Up Down Down N Up Up Down Up O Up Up Up Down This mode is useful in situations where a stereo output isn't feasible such as when outdoor speakers are used in a large area. Automatic detection of a local source SA3 only When a source is connected to the AUX INPUT jacks, you can set the amplifier to detect when that source is turned on, thereby automatically switching the amplifier from standby to on. The amplifier is shipped with this feature turned off. For local source automatic detection, set switch B up. Single and supplemental amplifiers If you want to cover a large area, such as an outdoor patio, requiring more than one set of speakers, you can install additional amplifiers. To clean the amplifier, use only a soft, dry cloth to remove dust from the outside of the enclosure. You may use a brush attachment on a vacuum cleaner to clean the hard-to-reach areas. DO NOT use any solvents, chemicals, or cleaning solutions containing alcohol, ammonia, or abrasives. It is commonly available at hardware stores. If you do use caulking, apply it only after the wires are connected and the knobs tightened down. Check the caulking annually, and reapply as needed.

<http://experience-hr.com/images/cara-format-manual-nokia-3110c.pdf>

For additional help, see the troubleshooting information in your system owner's guide. If the problem still exists, contact your Bose dealer to arrange for service, or contact Bose Customer Service. Refer to the address list enclosed in the product packaging for correct phone numbers. Disconnect the other cable from its speaker, and connect that end of the cable to the speaker that does not play. If the speaker still does not play, the problem is in the speaker. Connect it to the other outputs on the amplifier. If the speaker plays, the problem is in the original cable that was connected to that speaker. If the speaker does not play, the problem is in that channel of the amplifier. Details of the coverage are provided on the product registration card that came with the product. Please fill out the information section of the card and mail it to Bose. Failure to do so will not affect your warranty rights. If so, the sudden loss of volume was an intentional action of the amplifier's overload protection feature. This engages automatically if the volume is set too high and is overdriving the speakers. Choosing a lower setting should ensure continuous, even volume. Problem What to do We strive to reproduce the musical sounds as closely as possible to those of the original performance. While those sounds may be initially attractive to the novice, they are not real and are not enduring. In addition, we use only the highest quality parts and the latest assembly and quality control techniques to ensure the reliability and long life of our products. Our reputation rests on our steadfast pursuit of this policy in sound systems for the home, the automobile, and businesses. This enables us to support research that continually gives rise to new technologies for improving sound reproduction.

<http://experience-hr.com/images/cara-format-manual-nokia-7210-supernova.pdf>

When you purchase any product from Bose, we encourage you to compare it, as we do, to competitive products for musical accuracy. We believe that this process will enhance your appreciation of the product you select. Please check here if you do not want to be contacted regarding software upgrades. This limited warranty does not cover a defect that has resulted from improper or unreasonable use or maintenance, accident, excess moisture, improper packing, lightning, power surges, or unauthorized tampering, alteration or modification. Limitation on Liability THE PROVISIONS OF THIS LIMITED WARRANTY ARE IN LIEU OF ANY OTHER WRITTEN WARRANTY, WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. For how long The Bose Limited Warranty lasts one year from the purchase date for electronic products, systems, and powered speaker components, and five years for speaker components that are not selfpowered amplified. Integrated, stereo, and home theater systems have a one year

Limited Warranty. Powered component speakers have a one year Limited Warranty term for the electronics and five years for the speakers. The Headset X has a two year Limited Warranty, excluding the ear cushions, which have a 6 month Limited Warranty. Please see your Owners Guide for details. For the Limited Warranty on professional products, please refer to your Owners Guide for details. What we will do We will, at our sole option, repair or replace any defective parts within a reasonable period of time and free of charge. What we will not do Pay shipping or transportation charges from you to us. What you must do to obtain Warranty Service 1. Return product with proof of purchase from an authorized Bose dealer to a Bose Service Agency, or 2.

Return product with proof of purchase from an authorized Bose dealer directly to Bose Corporation. If you elect to return the product directly to Bose Corporation, the following procedures must be followed. If you need a new carton, contact Bose Corporation for a new carton available at a nominal charge; Warranty information continued on other side Other conditions This limited warranty gives you specific legal rights, and you may also have other rights which vary from country to country or state to state. This limited warranty is void if the label bearing the serial number has been removed or defaced. We know it will give you years of satisfaction. For your benefit, we recommend that you record your serial numbers, found on the products, and other purchase information on this card and keep it with your personal records along with proof of purchase. If necessary, this information will allow us to better serve your needs. Please send any correspondence regarding product information or warranty services to Bose Corporation, The Mountain, Framingham, MA 01701 916 850 8797 330 or tollfree 800 444 BOSE. Please do not offer the downloaded file for sell only use it for personal usage. Looking for other manual For this no need registration. May be help you to repair. You could suffer a fatal electrical shock. Instead, contact your nearest service center. Note! To open downloaded files you need acrobat reader or similar pdf reader program. In addition, Also some files are djvu so you need djvu viewer to open them. These free programs can be found on this page needed progs If you use opera you have to disable opera turbo function to download file. If you cannot download this file, try it with CHROME or FIREFOX browser. Translate this page Relevant AUDIO forum topics Bose Lifestyle CD20 FLC kijelzo halvány Sziasztok! A fenti készüléknek halvány a kijelzése. Eleg érdekesen van megoldva a kijelző tapfeszése, sokban függ a bejövő 12VAC feszültségtől.

tecsal.com.br/wp-content/plugins/formcraft/file-upload/server/content/files/1626e69bf20d91---bosch-hsw195aeu-manual.pdf

Kérdésem az lenne, hogy a fűtést próbáljam emelni, vagy a 24V-ot. A D8-on a 30V is kevesebb, de az AC 4.5V is. Melyik befolyasolja jobban a fénnyel. A fűtés, vagy a negatív tapfeszés Basszus végfoka 23mp múlva megfut vagy pozitívba vagy negatívba ha nincs a hangszóró rarakva, hangszóróval azonnal leáll, amikor a kimeneten eljut DC 4V-ig a védelem lekapcsolja a relét az érosítót. Mikor a MUTE hibát kerestem, volt olyan eset is, hogy nem futott meg a kimenet és szólt a basszus rendesen, de újból bekapcsoláskor ha nem halkítottam le a potit akkor kikapcsolt a relé, ha lehalkítottam akkor jó lett, de nagyon susogott, arra hasonlított mint amikor FM rádió nincs az állomáson, van egy közös mute tranzisztor az kapcsolja az összes többi, ha azt kicseréltem akkor is megmaradt a susogás, szerintem visszafelé jött valamelyik oldalról ezért szedtem ki mindegyik oldalról a tranzisztorokat, nem akartam bajlódni vele, hogy honnan jön a susogás vissza. Mi lehet a gond Bose Sounddock 1 tapegyseg csatl. Sziasztok. Egy barátom megkérte, hogy találjak vagy gyártsak egy tapegyseget a Bose dokkolójához. Sajnos az eredetiket aranyban adják, így gyártanom kell egyet. Találtam is egy elegáns kis 4 pines csatl., de fennakadtam az eredeti csatlakozó labkiosztáson. Találtam egy rajzot de nem tudom eldönteni, hogy a kábel levét ábrázolja, vagy a dokkolóban levét. Ha valakinek dolga volt ilyennel, és tudna segíteni, kérem ne tartsa vissza magát. Köszönöm.. BOSE bekötési rajz Legyszi legyszi ha valaki tudnasegíteni egy BOSE AMP2440-as érosító bekötésében, azt nagyon szépen megköszönöm. Ez AUDI A3-asból van, a steker nincs meg. Similar

manuals You can write in English language into the forum not only in Hungarian. Used GoodPlease try again.Please try again.Please choose a different delivery location.In order to navigate out of this carousel please use your heading shortcut key to navigate to the next or previous heading.

In order to navigate out of this carousel please use your heading shortcut key to navigate to the next or previous heading. Register a free business account Please try your search again later.Relax to classical music out on the deck while the kids watch a movie in the family room. At the same time, from the same Lifestyle system. Only Bose delivers this unique blend of performance, elegance, simplicity and expandability so you can enjoy a wholehome entertainment experience unlike any other. Bose link makes it possible. And the SA3 stereo amplifier makes it easy. Simply connect the speakers in the second area to the SA3 amplifier. Then connect the amplifier to the Bose link output on your Lifestyle media center with just one cable included. You can even enjoy Bose sound from a TV or separate CD player in the second areajust connect these sources to the SA3 amplifiers auxiliary input. The SA3 amplifier is easy to install, and you can even connect multiple amplifiers seamlessly to one Lifestyle system for up to 14 additional areas of soundindoors or outside. Patented Bose technology ensures highquality sound performance, automatically adjusting tonal balance. And you can control your entertainment easily in each additional area with a dedicated Lifestyle expansion remote control sold separately. The SA3 amplifier also offers a mono output option for speakers placed very far apart, and its small enough to be easily hidden on the floor or on a shelf. You can even mount it to a wall or a floor joist.Demant Sound USA, Inc.

Videos for related products 302 Click to play video Etymotic QSA Personal Sound Amplifier Manufacturer Video Videos for related products 452 Click to play video Douk Audio Tone Bluetooth Amplifier 2019 New Version DoukAudio Videos for related products 211 Click to play video Yamaha AS3000 Natural Sound Integrated Amplifier Manufacturer Video Next page Upload your video Video Customer Review BEST SURROUND SOUND SYSTEM 2020 Top 10 See full review Revisione Onsite Associates Program Amazon calculates a product's star ratings based on a machine learned model instead of a raw data average. The model takes into account factors including the age of a rating, whether the ratings are from verified purchasers, and factors that establish reviewer trustworthiness. Please try again later. Luke 5.0 out of 5 stars BOSE no longer services this model. Model received worked like new.I miss my old bose and these sa3sExcellent sellerPage 1 of 1 Start over Page 1 of 1 In order to navigate out of this carousel please use your heading shortcut key to navigate to the next or previous heading. WARNING The apparatus shall not be exposed to dripping or splashing, and objects filled with liquids, such as vases, shall not be placed on the apparatus. As with any electronic products, use care not to spill liquids into any part of the system. Follow all instructions. Bose proprietary Integrated Signal Processing technology, featured in the amplifier, provides full, rich stereo sound, even when the speakers are playing at low volumes. Power is applied when the power cord is installed and plugged into an AC mains receptacle. 2 VCA Local volume control connection jacks. For switches A, B, and C, see "Setting Up Advanced Features" on page 26. For switches 6 through 9, see "Setting up the amplifier room code" on page 25. SA3 A B C 6 7 8 9 SA2 C 6 7 8 9 5 LED status indicator The green LED indicates the operational state of the amplifier. See "Poweringup your system" on page 22.

Following this information you will find a section that describes how to set up the amplifier with your particular home entertainment system. Consider the following guidelines when selecting a location for your amplifier. CAUTION DO NOT mount the amplifier on surfaces that are not sturdy enough, or that have hazards concealed behind them, such as electrical wiring or plumbing. To make sure that this remote will work with your home entertainment system, do the following to check the house code setting. 1. Remove the remote control battery cover and locate the microswitches Figure 6. 2. Make sure that the house code settings switches 1, 2, 3, and 4 match the house code settings in your main room remote. See the list of locations and phone numbers included in the shipping carton.

DO NOT plug the amplifier into an outlet until you have completed all other connections. Doing so may cause damage to the equipment. CAUTION Make sure that the amplifier is disconnected from AC power before making speaker connections. Speaker cord consists of two insulated wires. Page 24 Setting Up Additional Rooms For Sound Setting up remote controls for other rooms To set up the RC18S or RC38S remote 1. Remove the remote control battery cover and locate the microswitches Figure 19. 2. Make sure that the house code settings switches 1, 2, 3, and 4 match the house code settings in your main room remote. 3. This remote is shipped from the factory set for room B. Page 25 Setting Up Additional Rooms For Sound Setting up the amplifier room code The room code of the amplifier must match the room code of the remote used in the room where the speakers are installed. The amplifier, which is designed only for indoor use, may become dusty over time. To clean the amplifier, use only a soft, dry cloth to remove dust from the outside of the enclosure. You may use a brush attachment on a vacuum cleaner to clean the hard-to-reach areas.

DO NOT use any solvents, chemicals, or cleaning solutions containing alcohol, ammonia, or abrasives. Check to be sure no wires are touching across terminals. Pagina 3 Important Safety Instructions. Ground All Outdoor Antennas. Pagina 4 Contents. Before you begin English Model AV28 media center setup Multiroom interface setup Model 20 music center setup Model 5 music center setup Pagina 23 Setting Up Additional Rooms For Sound. Setup guidelines for additional rooms Pagina 24 Setting Up Additional Rooms For Sound Pagina 25 Setting Up Additional Rooms For Sound. Setting up the amplifier room code Pagina 26 Setting Up Advanced Features English. Cleaning the amplifier English. Technical information Características del panel de control Identificación del sistema Encendido del sistema Pagina 50 Configuración de sonido en salas adicionales Pagina 51 Configuración de sonido en salas adicionales. Figura 18. Instalación de muestra de Pagina 52 Configuración de sonido en salas adicionales Pagina 53 Configuración de sonido en salas adicionales. Configuración del código de sala del amplificador Pagina 54 Configuración de las funciones avanzadas Limpieza del amplificador Información técnica Pagina 59 Table des matières Caractéristiques du panneau de connexion Identification du système Mise sous tension du système Figure 18. Exemple d'installation Pagina 81 Configuration pour la sonorisation de pièces supplémentaires. Configuration du code de salle de l'amplificateur Pagina 82 Configuration des fonctionnalités avancées Nettoyage de l'amplificateur Informations techniques USA Italia. Bose Corporation, The Mountain Bose S.p.A., Via della Magliana 876. Framingham, MA 01701 9168 00148 Roma. Framingham, MA 01701 9168 USA. The site may not work properly if you don't update your browser. If you do not update your browser, we suggest you visit old reddit. Press J to jump to the feed.

Press question mark to learn the rest of the keyboard shortcuts Log in sign up User account menu 2 Using an SA3 amp by itself I want to use the Aux input and power some speakers. The SA3 has a dip switch for local source auto select I think it is switch C. However there is a problem, you have no way of setting the volume. At most you can set the line level volume going into the SA3 by using a variable audio source phone, laptop, etc but this does not affect the final volume of the speakers. All you are doing is adjusting gain on the input, not the output. So yes, but actually no. If I knew the expected resistance range, I could just permanently set it to 50% or something. While it is common to place a potentiometer on the output stage, the SA3 doesn't do that. What I can't tell you however is what the default power output on the output stage after a power cycle. What that means is that if you interrupt power to the SA3 I cannot tell you if, without a BoseLink connection what volume level your speakers would be or if the SA3 will even power on the output stage without a signal from the BoseLink port. If you have a compatible Lifestyle system, the 2nd zone remote and something to plug into the RCAs, you can do some testing to see what happens after you set the volume with the 2nd zone remote, disconnect the BoseLink connection and then power cycle the SA3. Will be next weekend though. Some simple points Amp has AUX in, I believe it requires 500mw input to auto turn on, and after 60secs of less than 500mw it shuts off VCS is to control the output stage, I think it

works the opposite to what's mentioned by others, will work with any potentiometer, I have mine running with a 10k ohm one, I think 10k is max volume, if no potentiometer is used, then it only outputs about 25% volume. Don't use the source to adjust volume as it will shut off at lower volume levels, best to use the VCS with a potentiometer.

Also avoid the SA2 amps as they will require additional work to get up and running. Do you mean VCA I was thinking to just buy and setting it to the max then controlling the volume with a Chromecast Audio from my phone. Have a question about the Bose QC35. Discovered something you want to share about the new NC700 headphones. All rights reserved Back to top. Something went wrong. Packaging should be the same as what is found in a retail store, unless the item is handmade or was packaged by the manufacturer in nonretail packaging, such as an unprinted box or plastic bag. All Rights Reserved. User Agreement, Privacy, Cookies and AdChoice Norton Secured powered by Verisign.

<http://www.diamondsinthemaking.com/content/3l-manual>